

STRAND BATTEN SUSPENSION

SUSPENSIONS FOR BATTENS UP TO 36 ft. LONG

A 25	1½" Gas Barrel (to be 2 ft. longer than batten). (Weight per foot run 3 lbs.)	1s.-3d. per ft.	1-6
A 26	Bridles (three required)	13s.-6d. each	16-3
A 27	One-way Grid Pulleys (three required)	7s.-0d. "	8-9
A 28	Three-way Grid Pulleys (one required)	13s.-3d. "	15-6
A 29	5 cwt. Single Drum Winch (one required). (Weight 56 lbs.)	£3-7s.-6d. "	4-6-6
Alternatively :-			
A 30	5 cwt. Three-drum Winch (one required). (Weight 65 lbs.)	4-7s.-6d. "	5-7-6
A 31	¼" dia. Flexible Steel Wire Line	1-1s.-0d. per 100 ft.	1-4-0
A 32	⅝" dia. ditto	1-3s.-6d. "	1-7-6

NOTE.—If three-drum winch is installed, only ¼" diameter line is required. Both sizes required when single-drum winch is used.

A 33	¼" Bulldog Grips (twelve required)	6d. each	8
A 34	⅝" ditto (three required)	8d. "	10
A 35	¼" Thimbles (six required)	3d. "	4
A 36	⅝" ditto (two required)	4d. "	4
A 37	Swivel Shackles (one required)	6s.-9d. "	10-6

NOTE.—When the three-drum winch is used only the ¼" grips are required. Nine to be used.

SUSPENSIONS FOR BATTENS OVER 36 ft. LONG

A 25	1½" Gas Barrel (to be 2 ft. longer than batten). (Weight per foot run 3 lbs.)	1s.-3d. per ft.	1-6
A 26	Bridles (four required)	13s.-6d. each	16-3
A 27	One-way Grid Pulleys (four required)	7s.-0d. "	8-9
A 38	Four-way Grid Pulleys (one required)	18s.-0d. "	1-0-0
A 39	10 cwt. Single-drum Winch (one required). (Weight 168 lbs.)	£5-10s.-0d. "	7-10-6
Alternatively :-			
A 40	10 cwt. Four-drum Winch (one required). (Weight 2 cwts.)	7-7s.-0d. "	9-7-0

NOTE.—If four-drum winch is installed, only ¼" diameter line is required. Both sizes required when single-drum winch is used.

A 33	¼" Bulldog Grips (sixteen required)	6d. each	8
A 34	⅝" ditto (three required)	8d. "	10
A 35	¼" Thimbles (eight required)	3d. "	4
A 36	⅝" ditto (two required)	4d. "	4
A 37	Swivel Shackles (one required)	9s.-0d. "	10-6

NOTE.—When the four-drum winch is used only the ¼" grips are required.

12 Nine to be used.

COUNTERWEIGHT ROD SUSPENSION (for use when batten is suspended from existing counterweight lines).

A 41	Counterweight Clips	3s.-6d. each	5-9
------	----------------------------	--------------	-----

ASBESTOS SAFETY BORDER (with tapes for tying on to barrel behind spotlights). L.C.C. Regulations.

A 42	12' 0" x 2' 0" deep	£2 5s. 0d. each	
A 43	6' 0" x 2' 0" deep	1 2s. 6d. "	

STRAND ELECTRIC
AND ENGINEERING CO., LTD.

Telephone : Temple Bar 7464 (6 lines). Telegraphic Address : Spotlite, Rand, London.

FLORAL STREET, COVENT GARDEN, W.C.2