
Each

2 15 0

FLOOD and SPOTLIGHT STANDS

Wrought iron $\frac{3}{4}$ in. barrel screwed into cast iron base plate as illustrated. Fitted with extending liner of $\frac{3}{8}$ in. gas barrel with 3 in. diameter locking wheels and cable hook. Minimum height, 4 ft. 3 in. Maximum, 7 ft. 0 in.





£ s. d. L 60 Light pattern telescopic. 1 2 6 (Weight, 28 lbs.) If fitted with castors, rubber-tyred ... 2 3 6

L 66 Heavy pattern telescopic. (Weight, 37 lbs.) (I in. barrel, $\frac{1}{2}$ in. liner) If fitted with castors, rubber-tyred



L 112 Bench Base



L 113 Flange Plate Stand





L 79



LIII	Tripod stand, made up angle iron, with $\frac{1}{2}$ in.	p of l in. liner, 3 i	gas barre n. diame	el and light ter locking
	wheels, and fitted	with safe	ety pin.	Minimum
	height, 3 ft. 6 in.	Maximum	, 6 ft. U	in. (Nett
	weight, 17 lbs.)		***	

L	112	Heavy cast in	on bench	base with	locking	lever.		
		Height, 8 in.			•••		0	5

L	113	Flange plate stand with locking wheels and 4 in.			
		diameter base. Height, 6 in. (Nett weight, 2½ lbs.)	0	3	6

L	79	Swivel	arm	bracket	(extending	12 in.)	 •••	0	7	6

L 114 Knuckle arm	bracke	et with	two	joints	(extend	ding			
to 18 in.)	• • •		• • •	•••	•••	•••	I	3	0
Extra joints						• • •	0	6	0

L 115 Theatrical dressing table standard, 12 in. high, with 6 in. diameter heavy cast base.

B.C. holder, finished any colour 7 6 Nett

ELECTRIC STRAND AND ENGINEERING CO., LTD.

FLORAL STREET, COVENT GARDEN, W.C.2-

Telephone: Temple Bar 7464 (6 lines).