

# ARC LAMP CARBONS

Listed below are the carbons recommended for use in the arc lanterns shown on pages 40-44. In addition, Strand Electric are distributors for "Columbia" and "Kinarko" Kinematograph Carbons

## "SHIP" STAGE ARC CARBONS (D.C.)

Amperes	Diam. of Positive	Diam. of Negative	Arc Volts	PRICES Per Hundred			
				4½ in.		6 in.	
				Pos.	Neg.	Pos.	Neg.
Up to 40 amps. use "Ship" Stage Arc (S.A.), Positive No. 50 Cored (but not copper-coated) with Ship Stage Arc (S.A.), Negative No. 50 Solid (not copper-coated).							
10	8 m/m	5 m/m	48	9/9	7/6	13/-	10/-
20	15 m/m	8 m/m	48	24/9	9/9	33/-	13/-
25	16 m/m	9 m/m	48	25/6	12/-	34/-	16/-
30	18 m/m	10 m/m	50	33/9	14/3	45/-	19/-
40	20 m/m	12 m/m	50	39/6	19/6	53/-	26/-
From 50 to 120 amps. use "Ship" Stage Arc Positive No. 50 Cored (not copper-coated) or alternatively "Ship" Kino No. 7. Either of these positives with Kino No. 6 negative which is cored and copper-coated.							
50	20 m/m	8 m/m	52	—	—	53/-	25/-
60	20 m/m	10 m/m	52	—	—	53/-	29/-
80	22 m/m	11 m/m	52	—	—	63/-	32/-
100	25 m/m	12 m/m	54	—	—	87/-	34/-
120	28 m/m	14 m/m	56	—	—	105/-	38/-

## "SHIP" WHITE FLAME CARBONS (A.C.)

Amperes	Diameter	Arc Volts	PRICES Per Hundred	
			4½ in.	6 in.
"Ship" White Flame No. 61 carbons for A.C. projection.				
15-20	10 m/m	25-28	16/3	21/6
20-25	11 m/m	25-28	20/-	26/6
25-30	12 m/m	25-28	22/3	29/6
30-35	13 m/m	25-28	24/9	33/-
35-40	14 m/m	25-28	28/3	37/6
40-60	16 m/m	30-35	33/9	45/-
60-75	20 m/m	30-35	52/6	70/-
75-100	22 m/m	30-35	63/9	85/-

The same diameter carbon is used in both the upper and lower positions for A.C. work. Sometimes better results are obtained by using a carbon 1 m/m less in diameter in the lower position, as only one crater is used for projection work.

**STRAND ELECTRIC**  
AND ENGINEERING CO., LTD.

Telephone : Temple Bar 7464 (6 lines). Telegraphic Address : Spotlite, Rand, London.

**FLORAL STREET, COVENT GARDEN, W.C.2**