



SCALE 1:10

**WEIGHTS**

Patt 264 16 1/2 lb (7.5 kilos)  
 Patt 264W 16 3/4 lb (7.6 kilos)

**LAMPS & PERFORMANCE DATA**

	THROW DISTANCE		BEAM SPREAD		ILLUMINATION					
					1000W 120V Q1000T12/4CL or 1M/T12/2		1000W 240V Class T/4 or Philips 6291C		750W 120V 750T12/CL or 750T12/9	
	feet	metres	feet	metres	f.c.	lux	f.c.	lux	f.c.	lux
Pattern 264  BEAM ANGLE 17° in which intensity varies 2:1	30	10	9	3	83	750	73	650	56	500
	40	15	12	4.5	47	335	39	280	31	220
	50		15		30		25		20	
Pattern 264W  BEAM ANGLE 26° in which intensity varies 2:1	20	7	9	3	75	610	67	550	63	510
	25	9	12	4	48	375	43	330	40	310
	30		14		33		30		28	

**SPECIFICATION**

The spotlight shall be constructed of zinc coated steel pressings with baffled ventilation slots and aluminium die-castings and shall contain a prefocus lampholder, an ellipsoidal reflector, four individually operated soft-edge shutters, four individually operated hard-edge shutters and an adjustable lens.

The medium prefocus (P.28) porcelain lampholder for a 750 or 1000 watt base up burning tubular projection lamp shall be pre-tilted 30° from the vertical and shall be mounted on a removable assembly, normally secured by two captive thumb fasteners, and fitted with 30-in. (0.75m) heat-resisting 3-core flexible cable provided with a strain relief gland.

The 6 1/4-in. (160mm) diameter faceted ellipsoidal reflector shall be of polished anodised aluminium. Both sets of four shutters shall be of stainless steel and provided with external heat-resisting operating knobs. Gate runners shall be provided for the optional addition of an iris diaphragm.

The lens shall be recessed within a double skin tube with a fixed diaphragm and shall slide in two slots each with a heat-resisting knob. Double die-cast aluminium colour frame runners shall be provided and one 6 1/2 x 6 1/2-in. (165 x 165mm) metal colour frame supplied.

The lens fitted shall be as follows:

- att 264 - one 6 x 8-in. (150 x 200mm) plano convex.
- Patt 264W - one 6 x 8-in. (150 x 200mm) plano convex and one 3 1/2 x 9-in. (90 x 230mm) heat-resisting plano convex lens fitted to the fixed diaphragm.

The exterior shall be smooth finished with epoxy resin hard hammer grey and the interior, excepting reflector and gate shutters, flat black.

The spotlight shall be mounted in a reversible cadmium plated mild steel fork with friction disc tilt clamp and 3/8-in. bolt and wing nut for suspension.

**VARIATIONS available at time of manufacture**

Tilt and swivel scale indication.

**ACCESSORIES**

- Ref. 625. 12-leaf iris diaphragm.
- Ref. 644. 3 1/2 x 9-in. HRPC lens to convert Patt 264 to 264W