

HMI 2.5kW


**HMI 575W Accessories**

Cat No.	Description
27040	HMI 575W
28849	Colour Frame
28846	4-Leaf Barndoor
28201	7.5m Extension Cable
28844	Scrim Set (One Double Scrim, One Single Scrim, One Half Double Scrim, One Half Single Scrim)
28840	Cone Small
28841	Cone Medium
28842	Cone Large
25030	1200/575W Electronic Ballast
25220	575W Magnetic Ballast
28821	Flight Case
28401	Mechanical Dimmer
28843	Adaptor Cable to other 575W Ballasts

**HMI 1.2kW Accessories**

Cat No.	Description
27050	HMI 1.2kW
28859	Colour Frame
28050	4-Leaf Barndoor
28203	7.5m Extension Cable
28304	Scrim Set (One Double Scrim, One Single Scrim, One Half Double Scrim, One Half Single Scrim)
28850	Cone Small
28851	Cone Medium
28852	Cone Large
25030	1200/575W Electronic Ballast
25230	1200W Magnetic Ballast
28821	Flight Case
28401	Mechanical Dimmer
28402	DMX Dimmer

**HMI 2.5kW Accessories**

Cat No.	Description
27060	HMI 2.5kW
28093	Colour Frame
28114	4-Leaf Barndoor
28205	7.5m Extension Cable
28306	Scrim Set (One Double Scrim, One Single Scrim, One Half Double Scrim, One Half Single Scrim)
28090	Cone Small
28091	Cone Medium
28092	Cone Large
25040	2500/1200W Electronic Ballast
25050	4000/2500W Electronic Ballast
25240	2500W Magnetic Ballast
28821	Flight Case
28403	Mechanical Dimmer
28404	DMX Dimmer

**HMI 4kW Accessories**

Cat No.	Description
27070	HMI 4kW
28097	Colour Frame
28115	4-Leaf Barndoor
28207	7.5m Extension Cable
28307	Scrim Set (One Double Scrim, One Single Scrim, One Half Double Scrim, One Half Single Scrim)
28094	Cone Small
28095	Cone Medium
28096	Cone Large
25050	4000/2500W Electronic Ballast
25250	4000W Magnetic ballast
28822	Flight Case
28405	Mechanical Dimmer
28406	DMX Dimmer
28873	Adaptor Cable to other 4kW Ballasts

**HMI 6kW Accessories**

Cat No.	Description
27080	HMI 6kW
28889	Colour Frame
28886	4-Leaf Barndoor
28209	7.5m Cable
28884	Scrim Set
28880	Cone Small
28881	Cone Medium
28882	Cone Large
25060	6000/4000W Electronic Ballast
25260	6000W Magnetic Ballast
28822	Flight Case
28407	Mechanical Dimmer
28883	Adaptor Cable to other 6KW Ballasts



HMI 4kW



HMI 6kW

Location Luminaires

	Lux		Ø		Lux		Ø	
	5m	10m	7m	10m	10m	15.3	20.4	2.0
HMI 2500W (F 54°)	5280	5.0	1320	10.0	567	15.3	330	20.4
HMI 2500W (S 6.8°)	46400	0.5	11600	1.0	5155	1.6	2900	2.0

Typical performance based on 2500W HMI lamp.

	10m		15m		20m		25m	
	Lux	Ø	Lux	Ø	Lux	Ø	Lux	Ø
HMI 4000W (F 69°)	5280	5.0	1320	10.0	567	15.3	330	20.4
HMI 4000W (S 6.8°)	46400	0.5	11600	1.0	5155	1.6	2900	2.0

Typical performance based on 4000W HMI lamp.

	10m		15m		20m		25m	
	Lux	Ø	Lux	Ø	Lux	Ø	Lux	Ø
HMI 6000W (F 73°)	5280	5.0	1320	10.0	567	15.3	330	20.4
HMI 6000W (S 6.8°)	46400	0.5	11600	1.0	5155	1.6	2900	2.0

Typical performance based on 6000W HMI lamp.

	L	W	H	Ⓛ	Ⓜ	Ⓝ	Ⓞ	Ⓟ
HMI 2500W	366	455	752	13.0	22.5	-	270	
HMI 4000W	405	540	875	17.5	28.5	-	320	
HMI 6000W	600	725	1100	60.0	111.0	-	-	

 L Length W Width H Height Ⓛ Weight of product (kg) Ⓜ Packed weight (kg)  
 Ⓝ Packed volume (cu.metres) Ⓞ Colour filter cut size (mm) Ⓟ Beam diameter in metres  
 F Flood S Spot