

## SL Coolbeam Spotlights

SL Coolbeam spotlights have been designed to perform in today's tightly focused lighting rigs. These compact diecast construction spotlights run brighter and cooler than traditional theatrical profiles due to the cold mirror technology used in their reflector design.

All SL lights feature excellent light output, superb distribution and the smoothest soft edge available. The high efficiency dichroic glass reflector combines with coated aspheric lenses to deliver more light. You can rely on the Zoom SLs for sharp gobos, clean edges and crisp shutter focus. All SLs are easy to use and maintain.



SL10 Coolbeam  
Spotlight 600W

SL5 Coolbeam  
Spotlight 600W

### SL Architectural Spotlights

The SL Architectural spotlights utilise CDM lamps to bring the power and control of theatrical lighting to a wide range of architectural applications that require clean bright, controlled light with exceptional lamp life. Ideal for both mixed daylight and standard environments. Lamps are available to match warm tungsten or cooler daylight and may be used in conjunction with conventional incandescent and metal halide luminaires.

Black or white finish. Consult Strand for other colours.



#### SL Architectural Luminaires Operational Data

	SL19/26/36/50	SL15/32	SL23/50
Weight	6.8 kg	7.0 kg	6.9 kg
Packed weight	9.4 kg	9.8 kg	9.6 kg
Packed volume	0.075 m <sup>3</sup>	0.083 m <sup>3</sup>	0.08 m <sup>3</sup>
Dimensions	605x350x350 mm	605x350x350 mm	
Filter cut size	158x158 mm	158x158 mm	
<b>Ballast</b>			
Weight	1.5 kg	1.5 kg	1.5 kg
Packed weight	2.0 kg	2.0 kg	2.0 kg
Packed volume	0.01 m <sup>3</sup>	0.01 m <sup>3</sup>	0.01 m <sup>3</sup>

#### Lamp Data (all 150W)

Lamp type	Colour temp. (K)	Rated life hours (H)
CDM-T 150W/830	3000	12,000
CDM-T 150W/942	4200	12,000
CMH	3000	6000
HIT/G12-3K	3200	10,000
HIT/G12-4K	4000	10,000
BLV 225222	4200	6000
CDM-SA/T 150W/942	4200	9000