

# Coda II

Coda II 500 watt Cyc Lights are designed for both top and bottom cyclorama lighting applications. Coda II is modular in design and units may be linked together to form up to 4-compartment, 4-color units. Each light is packed with a single yoke and an expansion yoke for multi-unit applications. All Coda IIs include a color frame.



*Coda II cyc light 500W*

## Features

- Exceptionally even high-intensity beam distribution
- Up to 4 Coda IIs may be linked to form a single multi-cell unit. Single-sided hanging hardware is included with each light
- May be used for bottom or top light applications
- ETL, cETL listed, CE marked

## Weights & Dimensions


Weight	7.28 lbs	3.3 kgs
Height	12"	305 mm
Width	7.9"	200 mm
Length	12.2"	310 mm
Color frame size	9¾" x 8½"	248 x 216 mm

## SPECIFICATION SUBMITTAL


CONSULTANT <input type="text"/>	PROJECT NAME: <input type="text"/>	MODEL NUMBER   QUANTITY: <input type="text"/> <input type="text"/> <input type="text"/> <input type="text"/> <input type="text"/> <input type="text"/> <input type="text"/> <input type="text"/>
DATE: <input type="text"/>	PROJECT NUMBER: <input type="text"/>	APPROVED BY: <input type="text"/>

### Strand Cyclorama Lighting


#### Photometric Data




Coda II used as a toplight mounted 18' (5.5m) above stage level.




6' (1.83m) from backdrop. 6' (1.83m) center-to-center spacing, continuous run 500W lamps, FDN.



5' (1.5m) from backdrop. 5' (1.5m) center-to-center spacing, continuous run 500W lamps, FDN.



3¼' (1m) from backdrop. 3¼' (1m) center-to-center spacing, continuous run 500W lamps, FDN.




Coda II used as a groundrow standing on stage at 45° tilt.


#### Mounting Instructions:

Because the housings are symmetrical, it is necessary to observe the direction of the reflector when installing the units either as a top light or a groundrow.

#### Coda II Toplight



#### Coda II Groundrow



#### Ordering Information

Cat No	Description
14010	Coda II cyc light 230 volt w/ colour frame, no connector
14111	Coda II cyc light 120 volt w/ color frame & C-clamp, no connector

#### Optional accessories

18129	Coda II wire guard (spare)
18130	Coda II color frame (spare)
82003	Safety Cable 19 Inch, light duty
82010	Hook clamp
82019	C-clamp (spare) (Standard - for SL, Fresnelite, Nodes and Coda II)

#### Lamps

FDN	Coda II Lamp 500W 120V
K1	Coda II lamp 500W 230 V

#### Environmental Data

Max operating ambient temperature: 110°F  
IP rating: IP20

#### Electrical & mechanical data

Supply voltage: 120/220V 50/60Hz

Max lamp per compartment: 500W

Power cable: Individual compartments fitted with 3' (1 m) cable.

Coda II can be supplied to special order with 9-pin connector for 4-circuit operation.

Standards compliance: ETL, cETL, CE

Construction: Formed sheet steel assembled with machine threaded screws and rivets for high strength and light weight. Black powder coated epoxy paint finish

Reflector: Asymmetric multi-curve reflectors of high reflectivity textured aluminum for smooth cyclorama illumination.

Mounting/suspension: Flat steel yoke assembly

#### Operational data

Lamp access: Through front of open face of fixture after color frame and wireguard are removed.

Tilt adjustment: Tilt angle is set by heat-insulated lock handle.

<b>Strand Lighting, Inc.</b> 6603 Darin Way Cypress, CA 90630 Tel: (714) 230-8200 Fax: (714) 899-0042	<b>Strand Lighting Europe Limited</b> Unit 2 Royce Road, Fleming Way Crawley, West Sussex RH10 9JY Tel: + 44 (0) 1293 554010 Fax: + 44 (0) 1293 554019	<b>Strand Lighting Asia Limited</b> 20/F Delta House, 3 On Yiu Street Shatin, N.T. Hong Kong Tel: +852 2757 3033 Fax: +852 2757 1767	<b>www.strandlighting.com</b>
---	--	---	-------------------------------

© Philips Group 2008  
All rights reserved.  
The Company reserves the right to make any variation in design or construction to the equipment described. E&OE