

150/200W FLOODLIGHT

Small theatrical Floodlight with a symmetrical, extra-wide angle distribution suitable for close-range, even illumination of door, window or small-scale cyclorama backings; also ideal to provide a relatively low intensity wash of tinted light over the acting area to consolidate highlighting from spotlights especially where these are few in number



Dimensions Scale 1:10 290mm 240mm 325mm 240mm Carton size 380 x 270 x 270mm. Packed weight 5kg.

Order Codes

Patt. 137 150/200w Floodlight 200w 240v G.L.S. lamp, E.S. base (2720 lm, 1000 hr av. obj. life) 150w 240v G.L.S. lamp, E.S. base (1960 lm, 1000 hr av. obj. life)

20 071 02 34 102 0T


34 101 04

Performance

Typical performance, based upon 200w 240v General Lighting Service lamp, Single coil filament, 2720 lm.

½ peak angle 80°

½ peak angle 110°
825 peak candela (cd)



STrand 137

Specification

Lamphouse

Pressed steel housing with sprung-closed hinged lid over colour runners.

Fork

Mild steel, reversible, with handgrip knob for tilt clamp. Fork threaded and supplied with %—in. Whit bolt, washer and wingnut for suspension and swivel clamp.

Lampholder

E.27 (E.S.) Porcelain body, fitted with lm external length of 3 xl.5mm² conductor, toughened silicone rubber insulated and sheathed flexible cable secured by a strain-relief gland.

Reflector

215mm diameter, etched and anodised aluminium mounted on spring steel spider.

Colour Frame

Top-access double internal runners, with sprung-closed hinged lid; one 210 x 235mm colour frame supplied for 'Cinemoid'.

Finish

High temperature stoved texture black.

Lamps

200w or 150w E.27 (E.S.) base, General Lighting Service, clear.

Accessories

Additional 'Cinemoid' colour frame

27 240 09

