

Catalogue Ref.	Leaflet	Description	Watts	Lamp		Beam	Colour Frame Ref.	DIMENSIONS				Weight lbs.	Price	
				Class	Cap			Length A ft. in.	Depth B ins.	Height			£	s.
										C ins.	D ins.			
<b>STANDARD FOOTLIGHT (S Type) Wide Angle</b>														
SF.3	A.1	3-ft. 4 compartments...	60, 100 or 150	G/S	ES	120° approx.	240	3 0	9 ¼	9 ½	—	25	* 9	6 0
SF.6	A.1	6-ft. 8 "						6 0	9 ½	9 ½	—	45	* 15	16 6
SF.9	A.1	9-ft. 12 "						9 0	9 ¾	9 ¾	—	70	* 24	7 6
SF.12	A.1	12-ft. 16 "						12 0	9 ¾	9 ¾	—	93	* 31	5 6
SF.15	A.1	15-ft. 20 "						15 0	9 ¾	9 ¾	—	118	* 37	7 6
SF.18	A.1	18-ft. 24 "						18 0	9 ¾	9 ¾	—	141	* 44	1 6
SF.21 etc.	A.1	21-ft. and over ...						—	—	—	—	—	—	—
EXTRAS	A.1	Wired 4-colour circuits ...	—	—	—	—	—	—	—	—	—	—	—	—
	A.1	Tails 3 colour ...	—	—	—	—	—	—	—	—	—	—	—	—
	A.1	" 4 colour ...	—	—	—	—	—	—	—	—	—	—	—	—

(If BC holders are fitted 6d per compartment should be deducted, but only 60 or 100-watt lamps can be used)

\*Per length. †Per compartment. ‡Per ft. extra

<b>STANDARD BATTEN (S Type) Supplied with Reflectors in Medium Angle Position</b>														
<i>With suspension brackets for 1½-in. gas barrel or brackets with shackles for hooks</i>														
SB.3	A.13	3-ft. 4 compartments...	60, 100 or 150	G/S	ES	95° approx.	240	3 0	9	13	18	28	* 10	8 0
SB.6	A.13	6-ft. 8 "						6 0	9	13	18	48	* 17	4 6
SB.9	A.13	9-ft. 12 "						9 0	9	13	18	73	* 26	10 0
SB.12	A.13	12-ft. 16 "						12 0	9	13	18	96	* 33	19 0
SB.15	A.13	15-ft. 20 "						15 0	9	13	18	121	* 41	4 0
SB.18	A.13	18-ft. 24 "						18 0	9	13	18	144	* 47	13 9
SB.21 etc.	A.13	21-ft. and over ...						—	—	—	—	—	—	—
EXTRAS	A.13	Wired 4-colour circuits ...	—	—	—	—	—	—	—	—	—	—	—	—
	A.13	Tails 3 colour ...	—	—	—	—	—	—	—	—	—	—	—	—
	A.13	" 4 colour ...	—	—	—	—	—	—	—	—	—	—	—	—

(If BC holders are fitted 6d per compartment should be deducted, but only 60 or 100-watt lamps can be used)

\*Per length. †Per compartment. ‡Per ft. extra

Batten Pilots extra holder added to white circuit { ES holder† 15 6  
compartments, wired BC holder† 15 0

**CYCLORAMA BATTEN – Use standard batten above but with reflectors in wide angle position**

<b>GROUNDROW (S Type) Wide Angle (2-ft. 6-in. tails at both ends)</b>																		
<i>Single row with floor mounting brackets, wired 3-colour circuits</i>																		
SGR.6	E.21	6-ft. 8 compartments...	60, 100 or 150	G/S	ES	120° approx.	240	6 3	13 ½	11	—	58	23	11 6				
SGR.3	E.21	3-ft. 4 "						3 3	13 ½	11	—	36	16	12 0				
<i>Single row as above with castors, wired 3-colour circuits</i>																		
SGR.6/C	E.21	6-ft. 8 compartments...						6 3	13 ½	14	—	60	25	15 6				
SGR.3/C	E.21	3-ft. 4 "						3 3	13 ½	14	—	38	18	16 0				
<i>Double row with end frame and castors, wired 4-colour circuits</i>																		
DGR/6	E.21	6-ft. 16 compartments...						6 3	20	20 ½	—	121	45	12 0				
DGR/3	E.21	3-ft. 8 "	3 3	20	20 ½	—	68	31	13 0									

(Use of 6-ft. lengths is advised. The 3-ft. are used to make up the length, or in cases of acute curvature)

<b>JUNIOR GROUNDROW OR LENGTH OR BATTEN (L Type)</b>														
<i>Compartments at 6-inch centres with frames for colours. Wired 1-ft. tails</i>														
L.2	A.31	Single sided, wired 2 circuits ...	40, 60 or 100	Pearl or Frosted Silica	BC	Wide	312	3 0	4 ½	8 ½	—	23	6	17 6
509		Pair of suspension brackets (when used as batten, two 3-ft. lengths should be bolted together)	—	—	—	—	—	—	—	—	—	—	—	10 0

<b>JUNIOR FOOTLIGHT (Open Type)</b>																		
<i>With fixing brackets and colour clips, wired 1 circuit to connectors, no tails</i>																		
JF.6	A.1	6-ft. length ...	40 or 60	Frosted Silica	BC	Wide	250	6 0	4 ½	7 ¼	—	26	7	0 0				
JF.3	A.1	3-ft. extension ...						3 0	4 ½	7 ¼	—	13	3	13 6				
250	A.1	Colour Filter clips per doz. (spare) ...						—	—	—	—	—	—	—	—	—	doz.	2 6
234	A.1	Colour frames (optional) set of four ...						—	—	—	—	234	1 6	4	—	—	—	set