THYRISTOR UNIT DIMMERS

200/250 volt AC only.

Constant-rated variable-load Thyristor dimmers with substantial filter. Ratings are for tungsten filament lamps. A single load circuit, to be controlled by a dimmer lever, requires a Type TU. Two or more load circuits, to be controlled either collectively or individually by dimmer levers, require one Type MTU dimmer and Type TU for the remaining circuits. For Up, Down, or to Preset intensity control from parallel-connected push-button sets one Type PTU dimmer is required and Type TU for the remaining circuits.

ALL PRICES ARE SUBJECT TO 10% V.A.T.

Type TU.50	5000-watt max.	Order Code 01 00 504	£ 55·00
Type TU.20	2000-watt max.	01 00 208	40.00
Type MTU.50	5000-watt max.	01 01 501	56.00
Type MTU.20	2000-watt max.	01 01 205	41.00
Type PTU.50	5000-watt max.	01 02 509	71.00
Type PTU.20	2000-watt max.	01 02 202	56.00
2-lever control 4-lever control 6-lever control 8-lever control	box with terminals I box with terminals	05 00 116 05 00 124 05 00 140 05 00 167 05 00 183 05 00 203	9·00 9·60 13·00 16·20 19·60 21·40
		Charles participated in the control of the control	

For colour cycle dimmers see Mini-2 Auto range page 7

SLIDER DIMMERS 200/250v AC only. Graduated resistance windings. With scale, internal terminals and conduit/cable entry at base.

	Order Code	£
500/1000 watt	000 546 8	10.10
600/1200 watt	000 547 6	10.10
1000/2000 watt	000 548 4	20.00
500/1000 watt, top exit cord	000 556 3	10.10

ORCHESTRA LIGHTS

The orchestra stand is adjustable in height and has a lighting fitting with a B.C. lampholder and an adjustable spread shade. Supplied unwired.

Orchestra Stand	2611704	12.60
Lighting Fitting only	261180T	4.40

EXIT BOXES

5-in high EXIT characters (to B.S.2560). Complete with one B.C. and one E.S. porcelain lampholder, for primary and secondary lighting, opal diffuser and provision for 'Cinemoid' colour filter.

Surface mounting, EXIT	23 500 08	5.90
Surface, but with opal base	23 514 07	6.60
Flush mounting, EXIT	23 515 02	6.80
Surface, EMERGENCY EXIT	23 500 16	6.90
Surface, EMERGENCY EXIT		
opal base	23 514 15	7.60
Flush, EMERGENCY EXIT	23 515 10	7.80

UNDERWATER LIGHTING

GES underwater lampholder for 500 watt internally silvered lamp	Order Code	£
with 6½-in long 5-in dia. spigot	23 479 03	6.30
Colour filter holder assembly for above	23 476 07	1.20
Cinemoid colour filter cone for above	31 474 06	0.35

SPARE LAMPHOLDERS porcelain bodies

Bayonet Cap (B.22), recessed type, for Patt JF/3	27 490 04	0.30
Edison Screw (E.27), recessed type, for Patt JF/3, 137, S, S-/F	27 491 OT	0.35
Goliath Edison Screw (E.40) for Patt 49, 60, 543, 560	27 492 05	0.80
Medium Prefocus (P.28), for any Patt 23, 45, 123, 223, 263, 264	27 493 00	0.60
Large Prefocus (P.40) for Patt 93, 243, 253, 293	27 494 06	1.40
Bi-post (Bi 38) with lever lock, for Patt 243BP, 243TV, 152, 752	27 498 08	1.00
Medium Bipost (G.22) lampholder, for Patt 765	27 668 05	4.90
GX9·5 lampholder with heat-sink, for Patt 743, 750, 763/4, 773/4	27 734 06	4.00

SPARE LENSES

6×9-in PC lens for Patt 23N	27 304 06	3.70
6×8-in PC lens for Patt 263W and 264	27 306 07	4.10
3½×5-in PC lens for Patt 23, 23W, 52, 523, 523W	27 310 01	1.40
10-in dia. Fresnel lens for Patt 143, 243, 243BP, 543	27 317 OT	3.70
As above, but colouvred, for Patt 243/C	27 317 18	4.70
8×13-in PC lens for Patt 93, 253	27 369 07	9.50
4½-in dia. Fresnel lens for Patt 45	27 409 08	1.00
10×20-in PC lens for Patt 93N, 293	27 482 08	23.00
6-in dia. Fresnel lens (wide) for Patt 123	27 503 OT	1.60
As above, but colouvred for Patt 123/C	27 503 18	2.40
6×8-in colouvred Fresnel lens for Patt 263, 763F	27 623 09	2.00
8-in dia. Fresnel lens for Patt 223, 223TV Polestar, 743	27 634 01	2.80
As above, but colouvred for Patt 223/C, 743/C	27 634 1T	3.70
3½×9-in PC lens for Patt 263W, 264W	27 644 09	1.60
6×12-in PC lens for Patt 763W, 764W	27 698 07	5.00
10×40-in PC lens for Patt 765	27 699 02	29.00
8×26-in PC lens for Patt 773, 774	27 704 04	12.00
6×16-in PC lens for Patt 501, 763, 764	27 706 05	7.00

Rank Strand products are covered by a standard form of guarantee applicable to goods purchased and used within the United Kingdom.

Prices apply in U.K. only and are subject to the Company's TERMS AND CONDITIONS OF BUSINESS obtainable on request