

fresnel spots

These provide a soft-edged circular beam which is variable in spread from an intense near-parallel beam to a medium angle flood. Prices of Fresnel spotlights include tilting fork, one frame for colour, 1 metre external length of heat-resisting cable (except Polestar models) but *do not include* lamp, colour filter or suspension clamp.

	Order Code	£
Patt 45 250/500 watt, 4½-in dia. lens, 14°/45° beam spread, slide focus	20 03 008	11-00
Patt 123 250/500 watt, 6-in dia. lens, 26°/51° beam spread, slide focus	20 06 00T	19-50
4 door rotatable barndoor attachment	23 132 02	3-10




Patt 45 250/500 watt



Patt 123 250/500 watt

Patt 743 1000 watt halogen, 8-in dia. lens, 15°/82° beam spread, lead screw focus and GX9-5 holder for Class T/9 lamp	21 00 002	32-00
Coloured lens for Patt 743 or 223 (below)	27 634 1T	3-60
Patt 223 1000 watt, as above, but P.28s holder for Class T/6 lamp	20 11 008	26-00
4-door rotatable barndoor attachment for the Patt 743, 223	23 633 00	8-00
Patt 243BP 2000 watt halogen, 10-in dia. lens, 16°/50° beam spread, lead screw focus and Bipost lampholder for CP/41 tungsten halogen lamp	20 13 203	42-00
Coloured lens for Patt 243BP	27 317 18	4-70
4-door rotatable barndoor attachment for the Patt 243BP or 243TV	23 133 08	9-50


Patt 743 Polestar, GX9-5 holder for 1000 watt tungsten halogen lamp, 15°/82° beam spread, arranged for pole operation of pan, tilt and focus (hook coupling). Fitted with TV spigot, lens guard, carrying handles and internal terminal block	21 00 203	Apply
Patt 243 Polestar, Bipost holder for 2000 watt lamp, wide 18°/55° beam spread. Pole operation and fittings as above	20 13 404	Apply
8-ft pole for Polestar units, hook coupling	23 590 03	Apply
4-ft extension pole for 590	23 591 09	Apply



Patt 743 1000 watt tungsten halogen
Patt 223 1000 watt



Patt 243BP 2000 watt



Patt 750 1 000 watt tungsten halogen

BEAMLIGHT


Patt 750 1000 watt tungsten halogen, 10-in dia. parabolic reflector, 9°/18° near-parallel beam spread, lead screw focus and GX9-5 holder for Class T/9 lamp	21 01 00T	35-00
--	-----------	-------

mini-spots


Small, neat spotlights, for 12 volt 100 watt tungsten halogen lamps, providing adjustable beam distribution as employed in stage and studio lighting.

Each Minispot with an integral 240 volt input transformer is available for either ceiling mounting on a B.S.31 circular conduit box or for ceiling-fixed Lytespan 2 track. Even more compact Minispots (requiring an external, concealed transformer) are available for either ceiling or for wall mounting. Finish: black.

	Order Code	£
MINI-PROFILE		
Four built-in shutters provide accurate control of beam shape with hard or soft beam edges. 25° max. spread.		
Mini-Profile with integral transformer and ceiling-mounting plate	22 105 00	15-70
Mini-Profile with integral transformer and fused Lytespan 2 adaptor	22 105 35	18-30
Mini-Profile with ceiling-mounting plate (needs external transformer)	22 101 09	11-90
Mini-Profile with wall-mounting plate (needs external transformer)	22 101 33	12-00
240/12 volt 100 watt external transformer	22 677 05	3-50
100 watt 12 volt Rank Strand tungsten halogen lamp	34 017 18	1-61
Lens hood, optional clip-on accessory	22 666 02	1-00
Additional lens and slide-on mount to increase to 50° max. spread	22 670 07	1-30
Slide-on holder for 1½-in disc of 'Cinemoid' colour filter	22 671 02	0-40



Mini-Profile with integral transformer



Mini-fresnel with integral transformer

MINI-FRESNEL

Soft-edged beam, spread variable by rear push-pull knob

Mini-Fresnel with integral transformer and ceiling-mounting plate	22 106 06	14-90
Mini-Fresnel with integral transformer and fused Lytespan 2 adaptor	22 106 30	17-50
Mini-Fresnel with ceiling-mounting plate (needs external transformer)	22 104 05	9-80
Mini-Fresnel with wall-mounting plate (needs external transformer)	22 104 3T	9-90
240/12 volt 100 watt external transformer	22 677 05	3-50
100 watt 12 volt Rank Strand tungsten halogen lamp	34 017 18	1-61