




Profile Spots




Pattern 23



Model 823



T-Spot(2)



Model 808

PROFILE SPOTS

Profile spotlights have four built-in shutters and gate runners between the reflector system and the lens to provide accurate and convenient control of beam shape. Spread stated is for max. circle.

Bifocal spotlights have two sets of shutters to provide a combination of hard and soft edges to a shaped beam.

Prices of Profile, Bifocal and Follow Spotlights include tilting fork, one frame for colour 1m external length of heat-resisting cable but *do not include* lamp, colour filter, suspension clamp, or safety chain.

	Order Code	£
Patt 23 500W , 30° max, spread, 90mm dia. P.C. lens and P.28s holder for T/17 Halogen, or T/1 lamp	20 010 03	44.00
P.C. lens, 90 x 125mm, to convert to 40° spread	27 310 01	5.90
Step lens, 90mm dia. to convert to 35° dif-fused-edge spread	27 411 01	5.90
Conical narrow angle lens front to convert to 14° max. spread	23 355 02	29.50
Iris diaphragm, 12-leaf, for any Patt 23	23 363 09	6.00
Model 823 650W , 22° max. spread, 150mm dia. prismatic step lens, Cinemoid/Chromoid frame and P.28s holder for T/13 Halogen lamp	21 300 06	52.00
Iris diaphragm, 12-leaf, for model 823	23 363 09	6.00
Model 813 650W variable spread 20°/35° 150mm dia. P.C. front lens, Cinemoid/Chromoid frame, circular mask for 14°/20°, handle, and P.28s holder for T/13 Halogen lamp	21 301 01	77.00

	Order Code	£
T-Spot(2)64 1000W Bifocal , 22° max. spread. 150mm dia. P.C. lens, Cinemoid/Chromoid frame, handle, and removable lamp tray with GX9.5 holder for T/11 Halogen lamp	21 031 0T	98.00
T-Spot(2) 54 , as above, but 30° max. spread. P.C. lens, 90 x 230mm, to convert either of above to extra-wide 38° max, spread	21 032 05	102.00
P.C. lens, 90 x 430mm, to convert 22° spread to 30° spread	27 644 09	9.50
Set of three circular aperture masks	27 777 01	8.20
Iris diaphragm, 12-leaf, for T-spot (2) only	23 791 08	2.90
Spare lamp tray for T-spot (2) only	23 775 13	9.00
	27 795 13	23.50
Patt 774 1000W Bifocal , 12° max. spread, Twin 200m dia. P.C. lens, handle and GX9.5 holder for T/11 Halogen lamp	21 070 03	115.00
Iris diaphragm, 12-leaf, for Patt 774, also Patt 263, 264	23 625 04	8.50
Model 808 2000W variable spread , 14°/24° 200mm dia. P.C. front lens, Cinemoid/Chromoid frame, built-in 18-leaf iris diaphragm, handle, and removable lamp tray with GY.16 holder for CP/43 Halogen lamp	21 304 08	220.00
Hand-operated 4-colour magazine with Cinemoid/Chromoid frames for 808 or Patt 774	23 701 02	45.00
Spare lamp tray for model 808	27 496 07	27.50

Follow Spot


FOLLOW SPOT

Patt 765 1000W CSI Follow Spot, 14° max. spread. Twin 250mm dia. P.C. lens, built-in iris, horizontal and vertical strip shutters, handles, built-in EHT starter unit (220/240V 50Hz input) complete with external regulation unit and tripod stand


Hand-operated 4-colour magazine for Patt 765, also 253H, 793

Mechanical dimming shutter assembly for Patt 765

	21 050 09	625.00
	23 636 07	48.00
	23 740 06	52.00



Pattern 765



Mini Profile

Mini Spots

MINI SPOTS

Minispots with an integral 240V input transformer are for ceiling mounting on a circular conduit box. Even more compact Minispots, each requiring an external, concealed transformer, are available for either ceiling or for wall mounting. Finish: black.

Mini Profile

Four built-in shutters provide accurate control of beam shape with hard or soft beam edges. 25° max. spread.

Mini-Profile with integral transformer and ceiling-mounting plate

Mini-Profile with ceiling-mounting plate (needs external transformer)

Mini-Profile with wall-mounting plate (needs external transformer)

240/12 volt 100 watt external transformer

100 watt 12 volt Rank Strand halogen lamp

Lens hood, optional clip-on accessory

Additional lens and slide-on mount to increase to 50° max. spread

	22 105 00	27.00
	22 101 09	21.00
	22 101 33	18.50
	22 677 05	15.00
	34 017 18	2.54
	22 666 02	2.60
	22 670 07	3.50

Mini Fresnel

Soft-edged beam, spread variable by rear push-pull knob

Mini-Fresnel with integral transformer and ceiling-mounting plate

Mini-Fresnel with ceiling-mounting plate (needs external transformer)

Mini-Fresnel with wall-mounting plate (needs external transformer)

240/12 volt 100 watt external transformer

100 watt 12 volt Rank Strand halogen lamp

	22 106 06	23.00
	22 104 05	18.00
	22 104 3T	17.00
	22 677 05	15.00
	34 017 18	2.54