

**POLLUX™
FRESNEL
5000W**

- Powerful, lightweight 5000W studio fresnel
- Dual filament version available for 2.5kW/2.5kW or 1.25kW/2.5kW lamp
- Manual or pole-operated versions
- Manual version suitable for location lighting
- Stirrup fitted with 29mm spigot
- Rotary power switch fitted
- Lamp ordered separately
- Supplied in black with 4-leaf rotating barndoor, colour frame and 7 metre power cable

Pollux 5000W Fresnel

Powerful lightweight Fresnel with 250mm diameter lens suitable for studio or location lighting in Motion Picture or Television. Available in manual or pole operated variants. Requires a CP29 5000W lamp. Supplied with barndoor, colour frame, rotary power switch and 7 metres of 3-core cable.

W 5000W V 230/240V < 12.5°- 56.5° 16.5kg * 1850 Lux
 ◆ 17m 405mm dia. 22kg 0.159m³ ✓ EN60 598 2-17
 i 2.1.2

Cat No. Description

26340	Pollux 5000W, Manual Operation
26350	Pollux 5000W, Pole Operation

Pollux 2.5/5kW Fresnel

Variant of standard 5000W Pollux fitted with 4-pin lampholders to take dual filament lamps for extra flexibility. The 4-pin CP32 lamp has two 2.5kW filaments, the CP58 lamp has 1.25kW and 2.5kW filaments and the CP30 has two 1.25kW filaments. Supplied with barndoor, colour frame, rotary power switch (to switch between filament 1, filament 2, filament 1+2 or off) and 7 metres of 3-core cable.

W 5000W V 230/240V < 11°- 62° 16.5kg * 2450 Lux
 ◆ 14m 405mm dia. 16.5kg 0.159m³ ✓ EN60 598 2-17
 i 2.1.2

Cat No. Description

26360	Pollux 2.5/5kW, Manual Operation
26370	Pollux 2.5/5kW, Pole Operation

Pollux Accessories
Cat No. Description

43294	5000W 240V CP29 Lamp
43293	5000W 230V CP29 Lamp
43324	2.5/2.5kW 240V CP32 Lamp
43323	2.5/2.5kW 230V CP32 Lamp
43584	1.25/2.5kW 240V CP58 Lamp
43583	1.25/2.5kW 230V CP58 Lamp
43304	1.25/1.25kW 240V CP30 Lamp
43303	1.25/1.25kW 230V CP30 Lamp
28307	Scrim Set No.7 (full & half 50%; full & half 66%)
28074	Additional Barndoor, 4-Leaf Rotating
28075	Barndoor, 8-Leaf Rotating
28077	Outrig Colour Frame
28076	Spare Wire Mesh Guard
28094	Cone 155mm
28095	Cone 225mm
28096	Cone 275mm
28097	Additional Colour Frame
82002	Safety Bond, 50kg
82012	Hook Clamp to accept 29mm Spigot
81011	Hercules Stand, Black with Castors
81015	Goliath Stand, Black
81022	Atlas Stand, with Castors
82013	TV-Hook Clamp, 32-62mm to accept 29mm Spigot



VEGA 10kW

**VEGA™
FRESNEL
10kW**

- High power fresnel
- For the larger TV studios and location film work
- Manual or pole-operated versions
- Stirrup fitted with 29mm spigot
- Manual version suitable for location lighting
- Rotary power switch fitted
- Lamp ordered separately
- Supplied in black with 4-leaf rotating barndoor, colour frame and 7 metre power cable

Vega 10kW Fresnel

High-wattage studio Fresnel with 350mm diameter lens for Motion Picture and Television applications in studios or on location. Available in manual or pole operated variants. Requires a CP83 10000W lamp. Supplied with barndoor, colour/diffuser frame, rotary power switch, and 7 metres of 3-core cable.

W 10,000W V 230/240V < 12.5°- 47° 24kg * 1950 Lux
 ◆ 22m 405mm diam 31kg 0.245m³ ✓ EN60 598 2-17
 i 2.1.2

Cat No. Description

26380	Vega 10kW, Manual Operation
26390	Vega 10kW, Pole Operation

Vega 10kW Accessories
Cat No. Description

43834	10kW 240V CP83 Lamp
43833	10kW 230V CP83 Lamp
28307	Scrim Set No.7 (full & half 50%; full & half 66%)
28074	Additional Barndoor, 4-Leaf Rotating
28075	Barndoor, 8-Leaf Rotating
28077	Outrig Colour Frame
28076	Spare Wire Mesh Guard
28094	Cone 155mm
28095	Cone 225mm
28096	Cone 275mm
28097	Additional Colour Frame
81015	Goliath Stand, black
82002	Safety Bond, 50kg
82012	Hook Clamp to accept 29mm Spigot
82013	TV-Hook Clamp, 32-63mm to accept 29mm Spigot

A selection of operating poles is listed on Page 36



SILVER BULLET 20kW

**SILVER BULLET™ 20K ★NEW★
TUNGSTEN HALOGEN FRESNEL
20kW**

- Highest power tungsten halogen fresnel in the range
- Designed in Hollywood to provide intense single-source illumination for studio and location film work
- Stirrup fitted with 29mm spigot
- Requires lamp and inrush-current protection dimmer
- Supplied in silver with 4-leaf rotating barndoor, colour frame and short power cable

Silver Bullet 20kW Fresnel

High-output Fresnel with 625mm diameter lens. To maximise lamp life, and to provide dimming control, a special 20kW dimmer is required in addition to the 20kW lamp.

W 20kW V 230/240V

Cat No. Description

24470	Silver Bullet 20kW
-------	--------------------

Silver Bullet 20kW Accessories
Cat No. Description

43034	20kW 240V Lamp
43033	20kW 230V Lamp
73101	Dimmer Unit, 20kW, DMX/D54 Control
28300	Scrim Set No.6 (full & half 50%; full & half 66%)
28101	Additional Colour Frame
28100	Additional Barndoor
81025	Gladiator Wind-up Stand