



ARTURO 1500W



ARTURO 2000W



ARTURO 6000W

ARTURO™ SOFTLIGHTS 1250W, 2500W, 5000W

- A range of three tungsten halogen studio softlights for 1250W, 2500W and 5000W operation
- Accepts 189mm linear tungsten halogen lamps at 1250W, 1000W or 650W
- Suitable for studio and location
- Optical system ensures shadowless indirect fill light from secondary reflector design
- Asymmetric beam distribution gives constant illumination as a subject approaches the source
- Manual or pole-operated versions available
- Power switching reduces intensity without a change of colour temperature
- All units have easy access to lamps for replacement
- Supplied in black with, colour/diffuser frame and stirrup with 29mm spigot
- Eggcrate accessories available for extra beam control

Arturo 1250W Accessories

Cat No.	Description
43104	P2/10, 625W 240V Lamp
43103	P2/10, 625W 230V Lamp
43074	P2/7, 1000W 240V Lamp
43073	P2/7, 1000W 230V Lamp
43124	P2/12, 1250W 240V Lamp
43123	P2/12, 1250W 230V Lamp
28310	Eggcrate, Narrow Beam
28311	Eggcrate, Wide Beam
28312	Additional Colour Frame
81011	Hercules Stand, Black with Castors
81022	Atlas Stand with Castors
82002	Safety Bond, 50kg
82012	Hook Clamp to accept 29mm Spigot
82013	TV-Hook Clamp, 32-62mm to accept 29mm Spigot

Arturo 2500W

This Arturo is a 2.5kW dual power softlight with two lamps, switched individually, to give intensity control with constant colour temperature. Designed for 2 x 189mm linear tungsten halogen lamps of 1250W, 1000W or 625W. A three position rotary switch allows switching between one on, two on, or off. The pole-operated version includes geared control of pan and tilt with friction clutches to allow for manual override. Optional eggcrate accessories may be fitted for directional control of beam spread. Supplied complete with colour frame and 7.0m of power cable.

W 2500W V 230/240V < 64° x 99° 14kg ✱ 1000 Lux  
 ◆ 5m X 310mm x 510mm 23kg 0.244m³  
 ✓ EN60 598 2-17 i 2.3.4

Cat No.	Description
26520	Arturo 1.25/2.5kW, Manual Operation
26530	Arturo 1.25/2.5kW, Pole Operation

Arturo 2500W Accessories

Cat No.	Description
43104	P2/10, 625W 240V Lamp
43103	P2/10, 625W 230V Lamp
43074	P2/7, 1000W 240V Lamp
43073	P2/7, 1000W 230V Lamp
43124	P2/12, 1250W 240V Lamp
43123	P2/12, 1250W 230V Lamp
28313	Eggcrate, Narrow Beam
28314	Eggcrate, Wide Beam
28315	Additional Colour Frame
81011	Hercules Stand, Black with Castors
81022	Atlas Stand with Castors
82002	Safety Bond, 50kg
82012	Hook Clamp to accept 29mm Spigot
82013	TV-Hook Clamp, 32-62mm to accept 29mm Spigot

Arturo 5000W

This Arturo is a 5kW dual power softlight with four lamps, switched in pairs, to give intensity control with constant colour temperature. Designed for 4 x 189mm linear tungsten halogen lamps of 1250W, 1000W or 625W. A four position rotary switch allows switching between 1 pair, two pairs, or off. The pole-operated version includes geared control of pan and tilt with friction clutches to allow for manual override. Optional eggcrate accessories may be fitted for directional control of beam spread. Supplied complete with colour frame and 7.0m of power cable.

W 5000W V 230/240V < 68° x 105° 20.5kg ✱ 892 Lux  
 ◆ 7m X 410mm x 600mm 28kg 0.39m³  
 ✓ EN60 598 2-17 i 2.3.4

Cat No.	Description
26540	Arturo 2.5/5kW, Manual Operation
26550	Arturo 2.5/5kW, Pole Operation

Arturo 5000W Accessories

Cat No.	Description
43104	P2/10, 625W 240V Lamp
43103	P2/10, 625W 230V Lamp
43074	P2/7, 1000W 240V Lamp
43073	P2/7, 1000W 230V Lamp
43124	P2/12, 1250W 240V Lamp
43123	P2/12, 1250W 230V Lamp
28316	Eggcrate, Narrow Beam
28317	Eggcrate, Wide Beam
28318	Additional Colour Frame
81011	Hercules Stand, Black with Castors
81022	Atlas Stand with Castors
81015	Goliath Stand, Black
82002	Safety Bond, 50kg
82012	Hook Clamp to accept 29mm Spigot
82013	TV-Hook Clamp, 32-62mm to accept 29mm Spigot

A selection of operating poles is listed on Page 36.

Arturo 1250W

Designed for the small studio or as a location fill light, Arturo 1250W provides virtually shadowless diffused illumination. The pole-operated version includes geared control of pan and tilt with friction clutches to allow for manual override. Optional eggcrate accessories may be fitted for directional control of the beam spread. Supplied complete with colour frame, and 3.5m power cable with in-line switch.

W 1250W V 230/240V < 62° x 95° 11kg ✱ 1200 Lux  
 ◆ 3m X 220mm x 400mm 15kg 0.118m³  
 ✓ EN60 598 2-17 i 2.3.4

Cat No.	Description
26500	Arturo 1250W, Manual Operation
26510	Arturo 1250W, Pole Operation