

PRELUDE F WITH BARNDOORS



PRELUDE PC



PRELUDE 16/30



PRELUDE 28/40


PRELUDE™
650W

- Professional specification 650W spotlights
- Suitable for small to medium size venues
- High-performance optics
- Electrically-isolated during lamp replacement
- Dual-height stirrup
- Easy access for lens cleaning
- Insulated rear handle
- Supplied in black finish with 650W T26 lamp, colour frame, mounting fork with M10 wingnut and bolt, and detachable 1.5m power cable with plug fitted
- Available as either 240V version (with 240V lamp and 15A plug) or 230V version (with 230V lamp and Schuko plug)

Prelude F

Fresnel spotlight giving a 9° to 40° soft-edged variable beam with good distribution. Optional barn door accessory.

W 650W V 230/240V < 9° - 40° 3.5kg * 1040 Lux ◀ 8m
 X 150 x 150mm B 4.5kg 0.032m³ ✓ EN60 598 2-17 i 1.1.4

Cat No. Description

11104	Prelude F, 240V T26 650W Lamp, 15A Plug
11103	Prelude F, 230V T26 650W Lamp, Schuko Plug

Prelude PC

Compact spotlight giving a tighter beam and wider range of beam angles, from 7.5° to 55°. Optional barn door accessory.

W 650W V 230/240V < 7.5° - 55° 3.6kg * 800 Lux ◀ 8m
 X 150 x 150mm B 4.8kg 0.036m³ ✓ EN60 598 2-17 i 1.1.4

Cat No. Description

11114	Prelude PC, 240V T26 650W Lamp, 15A Plug
11113	Prelude PC, 230V T26 650W Lamp, Schuko Plug

Prelude 16/30

Zoom profile spotlight with variable 16° to 30° beam for medium throws. Excellent beam quality gives crisp gobo projection. Includes four integral beam-shaping shutters and slot for a gobo (pattern) holder or iris. Optional iris diaphragm or gobo holder and wire guard.

W 650W V 230/240V < 16° - 30° 6.5kg * 1000 Lux ◀ 8m
 X 150 x 150mm B 8.3kg 0.073m³ ✓ EN60 598 2-17 i 1.1.4

Cat No. Description

11124	Prelude 16/30, 240V T26 650W Lamp, 15A Plug
11123	Prelude 16/30, 230V T26 650W Lamp, Schuko Plug

Prelude 28/40

Zoom profile spotlight with a variable 28° to 40° beam, ideal for shorter throws and over-stage use. Includes four integral beam-shaping shutters and slot for a gobo (pattern) holder or iris. Optional iris diaphragm or gobo holder, and wire guard.

W 650W V 230/240V < 28° - 40° 6.3kg * 542 Lux ◀ 8m
 X 150 x 150mm B 7.7kg 0.065m³ ✓ EN60 598 2-17 i 1.1.4

Cat No. Description

11134	Prelude 28/40, 240V T26 650W Lamp, 15A Plug
11133	Prelude 28/40, 230V T26 650W Lamp, Schuko Plug

Prelude Accessories
Cat No. Description

41264	Additional T 26, 650W, 240V Lamp
41263	Additional T 26, 650W, 230V Lamp
18040	Barn door, 4-Leaf Rotating
18046	Iris 18-Leaf
18045	Holder for 'B' Size Gobos
18047	Lens Guard 25mm Mesh
18043	Additional Colour Frame, Card
18044	Colour Frame, Metal
82010	Hook Clamp
82000	Safety Cable, Light Duty (up to 16kg)