



NOCTURNE™

FLOODLIGHTS

500/1000W

- * Single unit symmetric distribution floodlight giving wide even lighting
- * Ideal for general internal floodlighting tasks in theatres and small studios
- * 500W version takes 118mm range of double ended lamps. 1000W version takes 189mm range
- * Spring tensioned colour frame for good filter life. Outrig colour frame accessory available for saturated colour use on 1000W model

Nocturne 500

Wide-angle, general purpose single unit 500W floodlight.

Cat No. Description

14104	Nocturne 500W, 240V Lamp, 15A Plug
14103	Nocturne 500W, 230V Lamp, Schuko Plug

Coda 500

Wide-angle 500W floodlight in single, 3 or 4 compartment units for even top or bottom lighting of up to 6m cycloramas when used 1.5m from backdrop, and on 1.5m centres.

Cat No. Description

14014	Coda 500/1 500W Cyc light, 240V Lamp, 15A Plug
14013	Coda 500/1 500W Cyc light, 230V Lamp, Schuko Plug
14034	Coda 500/3 500W, 3-unit, 240V Lamp
14033	Coda 500/3 500W, 3-unit, 230V Lamp
14044	Coda 500/4 500W, 4-unit, 240V Lamp
14043	Coda 500/4 500W, 4-unit, 230V Lamp

Coda 1000

Wide-angle 1000W single unit floodlight for even top or bottom lighting of cycloramas.

Cat No. Description

14024	Coda 1000W Cyc light, 240V Lamp, 15A Plug
14023	Coda 1000W Cyc light, 230V Lamp, Schuko Plug

Nocturne 1000

Wide-angle, general purpose single unit 1000W floodlight.

Cat No. Description

14114	Nocturne 1000W, 240V Lamp, 15A Plug
14113	Nocturne 1000W, 230V Lamp, Schuko Plug

Nocturne Accessories

Cat No. Description

18121	Barndoor, 500W
18122	Barndoor, 1000W
18123	Additional Colour Frame, 500W
18124	Additional Colour Frame, 1000W
18125	Outrig Colour Frame, 1000W
82010	Hook Clamp

Replacement Lamps for Nocturne

Cat No. Description

44014	K1 500W, 2900K, 240V Lamp
44013	K1 500W, 2900K, 230V Lamp
44044	K4 1000W, 3050K, 240V Lamp
44043	K4 1000W, 3050K, 230V Lamp

Coda Accessories

Cat No. Description

18121	Barndoor, 500W
18122	Barndoor, 1000W
18123	Additional Colour Frame, 500W
18124	Additional Colour Frame, 1000W
18125	Outrig Colour Frame 1000W
83100	Cable Gland, Coda 3 & 4 Cyc lights
83010	9 core 1.5mm Cable, (per m) Coda 3 & 4
82010	Hook Clamp
82000	Safety Cable, Light Duty (up to 16kg)

Replacement Lamps for Coda

Cat No. Description

44014	K1 500W, 2900K, 240V Lamp
44013	K1 500W, 2900K, 230V Lamp
44044	K4 1000W, 3050K, 240V Lamp
44043	K4 1000W, 3050K, 230V Lamp



Iris 1

For further information on Iris refer to page 34.

Supplied with:

1.5m heat resistant cable with 15A UK or Schuko plug; 230V or 240V 500W K1 or 1000W K4 lamp; Wire safety mesh; Metal colour frame.

Optional Accessories:

Barndoors for single compartment models; Outrig colour frame for 1000W model.

Throw	Lux 10m		Lux 15m		Lux 20m		Lux 25m		Lux 30m	
	Ø	Ø	Ø	Ø	Ø	Ø	Ø	Ø	Ø	Ø
Beamlite 500	6720	0.7	2987	1.1	1680	1.5	1075	1.8	746	2.2
Beamlite 1000	15500	0.8	3875	1.6	1722	2.5	969	3.3	620	4.1

Typical performance based on 500W E40 24V lamp (Beamlite 500) and 1000W K39d 24V lamp (Beamlite 1000).

	1m		2m		3m		4m		5m	
	Ø	Ø	Ø	Ø	Ø	Ø	Ø	Ø	Ø	Ø
Nocturne 500	4232	1.2	1028	2.3	470	3.5	264	4.7	169	5.8
Nocturne 1000	2074	2.7	922	4.1	518	5.5	331	6.8	230	8.2

Typical performance based on 500W K1 240V lamp (Nocturne 500) and 1000W K4 240V lamp (Nocturne 1000).

	L	W	H	Ⓜ	Ⓜ	Ⓜ	Ⓜ	Ⓜ	i
Beamlite 500	420	350	385	13.0	15.7	0.102	245	1.3.1	
Beamlite 1000	480	375	475	17.0	22.9	0.139	365	1.3.1	
Nocturne 500	210	280	320	3.7	4.5	0.027	214	1.4.3	
Nocturne 1000	210	350	320	4.3	5.0	0.033	285	1.4.3	

L Length W Width H Height Ⓜ Weight of product (kg) Ⓜ Packed weight (kg)
Ⓜ Packed volume (cu metres) Ⓜ Colour filter cut size (mm) i Strand data sheet reference number Ø Beam diameter in metres