Selecon ACCLAIM FRESNEL




The Acclaim 6°-60° Fresnel is a 300W / 575W / 650W general purpose Fresnel ($4\frac{1}{4}$ " diameter lens) for theatre, small studio and display lighting applications which produces an adjustable cone of light with a soft edge that is easily blended with adjacent beams to provide even illumination.

Selecon

ACCLAIM FRESNEL

FEATURES

- Up to 40% more light output than other Fresnels
- · Improved filter life through increased airflow
- Cooler focus operation due to the use of engineering plastics on front (color frame mount) and rea
- Adjustable yoke balance point
- 'Swing-down' side door for easy access to lamp or for cleaning
- Lamp life is enhanced through judder-free focus action of the captive lamp/reflector assembly which moves on Teflon-coated bearings
- Heat-insulated rear grab-handle which doubles as handy storage for the 3ft cable length.
- New barndoor design, cool to focus maintaining settings through unique hinge tension design
- Focusing is fast and safe using the large rear grab handle, heat protected focus knob and filter holder
- Built Selecon tough from aluminum extrusion and molded engineering plastics robust, dependable, safe and easy to rig
- Permanently attached integrated safety cable ensures that this important safety requirement is always on hand
- Integral micro-switch provides automatic power disconnection to the fixture when opening to relamp preventing a student or technician inserting a lamp into an electrically live fixture
- Three year warranty



Selecon

ACCLAIM FRESNEL


SOURCE								
Туре	FKW	Ushio WX	Ushio WC	FRK				
Wattage	300W	575W	575W	650W				
Average life (hrs)	200	300	1,500	300				
OPTICAL PERFORMANCE								
Output lumens	7,800			16,900				
BEAM								
Beam angle	6°-60°							
POWER								
Operating voltage	100-240VAC							
Wattage (max)	300	575	575	600				
PHYSICALS								
IP Rating	IP20							
Finish	Black							
Construction	Machined aluminum, sheet metal, and molded engineering grade plastic components							
ENVIRONMENT	°C		°F					
Ambient temperature	0-40		32-104					
DIMENSIONS	mm in							
HxWxL	298 × 217 × 32	26	11.75 x 8.5 x 12 7/8					
WEIGHT	kg		lb					
Net weight	3.36 7.4							
WARRANTY & APPROBATIONS								
Warranty	3 years							
Approvals / Listings	ETL / cETL listed to UL 1573							

Selecon

ACCLAIM FRESNEL

PHOTOMETRIC DATA

BEAM DIAMETER (ft)										
	6 °	0.0	0.7	1.4	2.2	2.9	3.7	4.4	5.1	5.9
	60°	0.0	8.1	15.0	24.2	32.3	40.4	48.5	56.6	64.7



LIGHT OUTPUT (footcandles*)								
	6 °	peak	876	254	97	55		
	60°	flat	103	30				

Tests conducted using a standard FRK, 650W, 120V lamp.

*for lux, mulitply footcandles by 10.7

PRODUCT NAME	ORDER CODE
Acclaim 4 Inch Fresnel, black	12ACFUS
Barndoor, 4 way, black	20BDMF
ACCESSORIES	
Lens safety mesh	15ACSM
Spare color frame	20CFMF
Spare US theatrical C-clamp	USCLAMP

For connector options please specify the following suffixes when ordering:

- -GR NEMA 5-15P Grounded Edison
- -GP 20A Stage Pin Plug

(ft)

-GTL NEMA L5-20P Twist-Lock

© 2018 Signify Holding. All rights reserved.

All trademarks are owned by Signify Holding or their respective owners. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Data subject to change.

Ref: 12ACFUS-100-00