PHILIPS Selecon

Hui Work Light



For overstage, rehearsal lighting the Hui Work Light provides a compact 90° flood beam.

The fixture is equpped with a wire safety mesh instead of safety glass which allows the air flow system to work in any position for extended operating hours.

This model is not suitable for use with plastic color filters; there is no color frame supplied.

Features

The Hui Work Light uses the FCL 500W, EHM and EHZ 300W 4 11/16th" lamps.

Re-lamp without having to break focus.

Shape the beam and contain glare with the four way accessory – fits all models.

Permanently attached safety cable ensures that this important safety requirement is always on hand.

Integral micro-switch provides automatic disconnection of power to the fixture when opening to relamp, preventing a student or technician inserting a lamp into an electrically live fixture.

Three year warranty.

Approvals

ETL / cETL listed to UL 1573.

Physical Data

Weight: 1-Batten Work Light 9lbs

AC supply cable: 36"

Included: 1x safety cable, 1x C-clamp and instruction leaflet.


Lamps: 120V

500W FCL 10,950 lumens,	2,000hrs average life
300W EHM 5,950 lumens,	2,000hrs average life
300W EHZ 5,900 lumens,	2,000hrs average life

Ordering Information

12HUIWK	HUI Work Light 1-Batten, black
15HUIBD 15HLWKCAS	Bbarndoor, 4 way, black Spare color cassette (with safety mesh)
USCLAMP	Spare US theatrical C-clamp

For connector options please specify the following suffixes when ordering: -GR NEMA 5-15P Grounded Edison -GP 20A Stage Pin Plug -GTL NEMA L5-20P Twist-Lock



© Philips Group 2010

All rights reserved.

The Company reserves the right to make any variation in design or construction to the equipment described. E&OE 100411NA

SPECIFICATION SUBMITTAL

CONSULTANT:	PROJECT NAME:	MODEL NUMBER QUANTITY:
DATE:	PROJECT NUMBER:	APPROVED BY: