


CANTATA™ Fresnel & PC 1200W


Features

The Cantata range combines all the features and performance criteria demanded by the professional theatre to become the 1.2kW spotlights of choice for lighting professionals.

- Range comprises Fresnel and PC Spot
- All models feature drop down lamp tray for easy lamp access and reflector cleaning
- Mains supply isolated when lamptray opened
- Easy to use lamp adjustment on profiles
- Durable construction of pressure die cast and extruded aluminium







Weights and dimensions

	F	PC
Weight	5.8kg	7.2kg
Packed weight	7.7kg	9.1kg
Packed length	530mm	600mm
Packed width	390mm	390mm
Packed height	390mm	390mm

Operational features

Lamp Access

Through drop down lamp tray secured by quarter turn fastener. Lamp tray can only be opened after removal of power connector ensuring full electrical isolation.

Focus Adjustment

By rotary control on rear of lamphouse

Lamp Adjustment

Lamp alignment adjusted by screwdriver on rear panel. Adjustment provided on all models for shorter LCL of T19 1000W lamps by alternative slide-in lampholder location

Mechanical/electrical data

Construction

Pressure die cast front and rear panels with extruded aluminium side panels and mild steel infill panels all finished in black epoxy powder coating.

Lenses

Heat resistant borosilicate lenses mounted in die cast front panel.

Lampholder


GX9.5 to take lamps of 67 mm LCL (55 mm in alternative lampholder location) and maximum of 1200W

Supply Voltage


230V +/- 10% 50/60Hz




Photometric data








Cantata PC: Narrow



Cantata PC: Wide



To calculate lux levels at any throw distance divide the following factors by the distance squared:

F PC
N W N W
Lux 132243 17715 195652 14238
e.g. Cantata PC at full flood over 12m throw 14238/144 = 98.9Lux

To calculate beam diameters at any throw distance multiply the throw in metres by the following factors:

Ordering information

Cantata spotlights are supplied complete with 1.5m of detachable cable with IEC 320 appliance connector and fitted plug, metal colour frame and T29 1200W lamp. 240V models come with 15A plug and 240V lamp. 230V models come with Schuko connector and 230V lamp.

Cat No	Description	Optional accessories	
12034	Cantata F, 240V	18104 Additional colour frame, metal	
12033	Cantata F, 230V	18106 Barndoor, 4 leaf rotatable	
		82001 Safety cable, heavy duty	
12044	Cantata PC, 240V	(NB it is recommended that Cantata profiles are rigged using the heavy	
12043	Cantata PC, 230V	duty safety cable)	
	·	82010 Hook clamp	
		55001 Colour Call scroller CC1	
		41293 Additional T29 lamp 1200W, 3050K, 400Hr - 230V	
		41294 Additional T29 lamp 1200W, 3050K, 400Hr - 240V	

The Company reserves the right to make any variation in design or construction to the equipment described. © Strand Lighting Ltd 1998.

Strand™, Strand Lighting™, Strand Quartzcolor ™ are trade marks of Strand Lighting Limited and Strand Lighting Inc.

Strand Lighting Ltd North Hyde House Hayes Rd Heston Middx UB2 5NL UK Tel: +44 (0)181 571 3588 Fax: +44 (0)181 571 3305 Strand Lighting GmbH Ullsteinstrasse 114-142 D-12109 Berlin Germany Tel: +49 (0) 30/70 79 51 0 Fax: +49 (0) 30/70 79 519 9 Strand Lighting Italia srl Via delle Gardenie 33 00040 Pomezia-Roma Italy Tel: +39 06 9147123 Fax: +39 06 9147136 Strand Lighting Asia Ltd 7/F Corporation Square 8 Lam Lok Street Kowloon Bay Hong Kong Tel: +852 2757 3033 Fax: +852 2757 1767

LONDON - BERLIN - ROME - PARIS - MOSCOW - LOS ANGELES - NEW YORK - TORONTO - HONG KONG