

NOCTURNE™ *500W & 1000W* CODA™ *500W & 1000W*


Nocturne

- ☐ Single unit symmetric distribution floodlight
- ☐ For general internal floodlighting
- ☐ In two versions: 500W and 1000W
- Wide, even distribution
- Barndoor option
- □ Supplied in black finish with lamp, colour frame, integral wire safety mesh, mounting fork with M10 wingnut and bolt, 1.5m cable with plug
- Available as either 240V version (with 240V lamp and 15A plug) or 230V version (with 230V lamp and Schuko plug)


Coda

- ☐ Single unit and compartment cyclorama floodlights with asymmetric distribution
- ☐ For even coverage of backcloths and cycloramas
- ☐ In two versions: 500W and 1000W
- Wide, asymmetric distribution


Coda 500W Nocturne 500W




Coda 1000W Nocturne 1000W



Coda 500W/3



Coda 500W/4



Weights and dimensions

| | Nocturne | Nocturne | Coda | Coda | Coda | Coda |
|-----------------|---------------|--------------------|-------------------|---------------------|---------------|-------------|
| | 500 | 1000 | 500/1 | 500/3 | 500/4 | 1000 |
| Weight | 3.80kg | 4.3kg | 3.80kg | 8.4kg | 11.0kg | 4.3kg |
| Packed Wt | 4.5kg | 5.0kg | 4.5kg | 9.2kg | 11.5kg | 5.0kg |
| Packed Vol | $0.027m^{3}$ | $0.033 m^3$ | $0.027 m^3$ | 0.073m ³ | $0.095 m^3$ | $0.033 m^3$ |
| Filter Cut Size | Nocturne & Co | oda 500, 500/3, 50 | 00/4: 214 x 240mm | Nocturne & | Coda 1000: 28 | 5 x 240mm |
| | Nocturne & Co | oda 500, 500/3, 50 | 00/4: 214 x 240mm | Nocturne & | Coda 1000: 28 | 5 x 240mm |



Photometric data

Typical performance based on 500W K1 240V lamp (Nocturne and Coda 500) and 1000W K4 240V lamp (Nocturne and Coda 1000)

At 5.5m hanging. 45° angle. 1.5m from cyclorama on 1.5m centres* Floor level 45° angle. 1.5m from cyclorama on 1.5m centres**


Coda

| Cyc Height (metres) | 1 | 2 | 3 | 4 | 5 | 6 |
|---------------------|------|------|------|------|------|-----|
| 500W* | 480 | 760 | 990 | 1000 | 1000 | 700 |
| 1000W** | 2050 | 1760 | 1100 | 580 | 360 | 270 |

Nocturne 500

Distance (m) 1 2 3 4 5 6 Beam Ø(m) 1.16 2.33 3.49 4.66 5.83 6.99 Illum (lux) 4232 1028 470 264 169 117

Nocturne 1000



Peak Intensity, 1/2 Peak and 1/10 Peak

| | ¹ /2 Pk | ¹ /10 Pk | Pk. Candelas |
|----------------|--------------------|---------------------|--------------|
| Nocturne 500W | 60.5 | 95.8 | 4232 |
| Nocturne 1000W | 68.6 | 99.5 | 8297 |

For performance at any distance divide candela by distance² For performance of Coda 1000W unit refer to your Strand Lighting dealer



Ordering information

Nocturne 500

Wide-angle, general purpose single unit 500W floodlight. Supplied with K1 500W lamp.

Cat No Description

14104 Nocturne 500W, 240V lamp, 15A plug

14103 Nocturne 500W, 230V lamp, Schuko plug

Nocturne 1000

Wide-angle, general purpose single unit 1000W floodlight. Supplied with K4 1000W lamp.

Cat No Description

14114 Nocturne 1000W, 240V lamp, 15A plug

14113 Nocturne 1000W, 230V lamp, Schuko plug

Coda 500

Wide-angle 500W floodlight in single, 3 or 4 compartment units for even top or bottom lighting of up to 6m cycloramas when used 1.5m from backdrop, and on 1.5m centres. Supplied with 500W K1 lamp(s).

Cat. No. Description

14014 Coda 500/1 500W cyclight, 240V lamp, 15A plug

14013 Coda 500/1 500W cyclight, 230V lamp, Schuko plug

14034 Coda 500/3 500W, 3-unit, 240V lamps

14033 Coda 500/3 500W, 3-unit, 230V lamps

14044 Coda 500/4 500W, 4-unit, 240V lamps

14043 Coda 500/4 500W, 4-unit, 230V lamps

Coda 1000

Wide-angle 1000W single unit floodlight for even top or bottom lighting of cycloramas. Supplied with 1000W K4 lamp. Optional outrig colour frame accessory.

Cat. No. Description

14024 Coda 1000 W Cyclight, 240V lamp, 15A plug

14023 Coda 1000 W Cyclight, 230V lamp, Schuko plug

Coda/Nocturne Accessories

Cat. No. Description

| 44014 | Additional K1 500W 240V lamp | 18123 | Additional colour frame, 500W |
|-------|-------------------------------|-------|---------------------------------------|
| | Additional K1 500W 230V lamp | 18124 | Additional colour frame, 1000W |
| | Additional K4 1000W 240V lamp | 18125 | Outrig colour frame 1000W |
| | Additional K4 1000W 230V lamp | 83100 | Cable gland, Coda 3 & 4 cyclights |
| | Barndoor, 500W | 83010 | 9 core 1.5mm cable, Coda 3 & 4 |
| | Barndoor, 1000W | 82010 | Hook Clamp |
| 10122 | Danidooi, 100011 | 82000 | Safety cable, light duty (up to 16kg) |

Operational features

Lamp access

Through the front of each unit or compartment via hinged wireguard with positive spring retention clip

Beam shaping

On single units only, 4-leaf barndoors

Tilt/Pan

Heat insulated hand knob on right side of luminaire. Single units: M10 bolt through top of fork. Multiple units: Swivel crossbar and M10 bolt.

Electrical & mechanical data

Construction

Pressure diecast zinc alloy end sections common to all luminaires joined by machine threaded screws to pressed sheet steel housing. High temperature stoved epoxy powder coat in black.

Anchorage provided for safety bond.

Mounting and suspension

Single units: Fork of aluminium alloy, reversible, with 70mm diameter friction disk and heat insulated hand knob. Fork threaded and supplied with M10 bolt, washer and wingnut Coda 500/3 & 500/4. Fitted with reversible 'L' forks, dual top suspension fork/groundrow tilt foot each with 70mm diameter friction disk and hand knob (Two hook clamps required for hanging unless swivel cross-bar is used).

Supply voltage

230/240 volts 50/60 Hz

Standards

Designed to conform to EN 60-598 2-17

The Company reserves the right to make any variation in design or construction to the equipment described. © Strand Lighting Ltd 1998.

Strand™, Strand Lighting™, Strand Quartzcolor ™ are trade marks of Strand Lighting Limited and Strand Lighting Inc.

Strand Lighting Ltd North Hyde House Hayes Rd Heston Middx UB2 5NL UK Tel: +44 (0)181 571 3588 Fax: +44 (0)181 571 3305 Strand Lighting GmbH Ullsteinstrasse 114-142 D-12109 Berlin Germany Tel: +49 (0) 30/70 79 51 0 Fax: +49 (0) 30/70 79 519 9 Strand Lighting Italia srl Via delle Gardenie 33 00040 Pomezia-Roma Italy Tel: +39 06 9147123 Fax: +39 06 9147136 Strand Lighting Asia Ltd 7/F Corporation Square 8 Lam Lok Street Kowloon Bay Hong Kong Tel: +852 2757 3033 Fax: +852 2757 1767

LONDON - BERLIN - ROME - PARIS - MOSCOW - LOS ANGELES - NEW YORK - TORONTO - HONG KONG