

THE COMPACT CONTROLLABLE SPOT

Now, from Rank Strand, a powerful lightweight spotlight for display lighting, in a range of colours, offering instant beam adjustment from spot to flood. No need to change fixed spread PAR lamps to suit the beam to the need;



Simple adjustment from spot to flood.

a simple focusing control varies the circular beam between 12° and 50°. A fourleaf barndoor can be added to shape the beam edges.

'Minim' can be ceiling, wall or track mounted and is easily adjustable both vertically and horizontally for accurate positioning of its closely controllable variable beam.


'Minim' is supplied complete with a 300 watt 2000 hour, long life TH lamp.
'Minim' exception in any

'Minim' excels in any indoor application: Shops, showrooms, salons, museums, studios, theatres, galleries, exhibitions etc., in fact any situation where there is a need



for creative display lighting.
Rank Strand, the world's leading specialists in stage lighting, now bring the technology that the Theatre and Television industries take for granted to a wider

audience.



Minim fitted with conversion bracket for track adaptor.





Rank Strand Limited, PO Box 51 Great West Road, Brentford, Middlesex TW8 9HR, Telephone 01-568 9222.

Telex 27976.

SPECIFICATION

Housing
Extruded, finned, aluminium sides, with steel top and bottom which incorporate multiple ventilation slots and light baffles. Heat insulated grab handle fitted at rear.

Environment
Designed for normal interior use.

Lampholder GY9.5 unequal pin.

80mm diameter short-focus Fresnel.

Reflector

80mm diameter spherical anodised aluminium.

Beam Adjustment Variable by an heat insulated thumbscrew on base of luminaire.

45° above horizontal to 90° below.

Finish

Semi-gloss high temperature stoved enamel.

Lamps

Supplied with an M/38 300 watt 220v or 240v GY9.5 base lamp. 500 watt lamps available but not recommended for colour finish luminaires.

Dimensions

195mm height × 165mm width × 175mm depth, including handle.

Weight

1.8 Kg.

Packaging

Supplied in a standard pack of 2 including lamps (state 240 or 220v).

Accessories

Light controlling 4-door rotatable barndoor.

Universal mounting bracket for both wall and ceiling mounting. Conversion bracket for ceiling track adaptor.





The Company reserves the right to make any variation in design or construction to the equipment described.