

GRID

The M-R Type 65 grid, is a complete unit and has been designed for compact and easy mounting on to the M-R Type S.65 stand.

This feature reduces to a minimum the floor space occupied by the lamp, and permits ready removal of the grid for taking above when the lamp head is mounted on overhead rails.

SPECIFICATION

Elements: Edge-wound strip type.

Housing: Cast aluminium end plates. Sheet metal casing amply provided with ventilation holes. Two handles at top for carrying.

Cables: Secured to and supplied with grid.

Mains supply: 25 ft. of Duracord cable provided with Technicolor lugs for supply.

Lamp head: Two 7 ft. lengths of heavy-duty, asbestos covered, flexible cable fitted with sockets for connection to lamp head.

Finish: Aluminium parts, natural (wire brushed); other parts, aluminium paint.

Overall Dimensions: Diameter 1 ft. 0 in. (30 cms.) Height 1 ft. 11¼ in. (50 cms.),

Weight: 46½ lb. (21 kg.) complete with cables.

STAND

The M-R Type S.65 stand is a single-lift type, and has a three-arm base equipped with rubber-tyred casters and a central support column.

The column is telescopic and provision is made for mounting the M-R Type 65 grid; three handles are fitted for securing the lamp head yoke, the grid, and for clamping the height setting.

For storage or transport purposes, the stand can be readily dismantled into a compact unit.

SPECIFICATION

Construction: Steel tubing with brass fittings. Ball bearing casters with rubber-tyred wheels.

Socket: 1⅛ in. (28.5 mm.) dia.

Finish: Black baked enamel; sliding surfaces plated.

Height from ground to socket: Minimum 2 ft. 10¼ in. (87 cms.) Maximum 5 ft. 0 in. (153 cms.).

Weight: 25¾ lb. (11.7 kg.).

OUR EXPERIENCE IS AT YOUR SERVICE