


# **500W FLOODLIGHT**



General-purpose theatrical Floodlight with a symmetrical, wide angle distribution suitable for small scale cyclorama lighting if spaced at least 2.5m from the cloth or wall; also for close range illumination of door and window backings.

Internal colour frame runners with a sprung-closed lid ensure that there is no external side scatter or rearward reflection off the colour filter.

# Dimensions Scale 1:10 400mm 325mm 380mm 370mm 370mm Carton size 420 x 360 x 350mm Packed weight 7.lkg


# **Order Codes**

Patt. 60 500W Floodlight 500W 240v G.L.S. lamp (7,700 lm, 1000 hr. av. obj. life) 20 050 02 34 104 00

# Performance

Typical performance, based upon 500W 240v General Lighting Service lamp, single coil filament, 7,700 lm.

½ peak angle 42° ½ peak angle 78° 8,500 peak candela (cd).



The Company reserves the right to make any variation in design or construction to the equipment described.

# STrand 60

# **Specification**

# Lamphouse

Pressed steel housing with full width baffled ventilation slots at rear and sprung-closed hinged lid over colour runners.

### Fork

Mild steel, reversible, with handgrip knob for tilt clamp. Fork threaded and supplied with %-in. Whit. bolt, washer and wingnut for suspension and swivel clamp.

# Lampholder

E.40 (G.E.S.) porcelain body, fitted with lm external length of 3 x 1.5mm<sup>2</sup> conductor, toughened silicone rubber insulated and sheathed flexible cable secured by a strain-relief gland.

# Reflector

265mm dia. planished, etched and anodised aluminium.

### Finish

High temperature stoved texture black.

### **Colour Frame**

Top-access double internal runners, with sprung-closed hinged lid; one 300mm square colour frame supplied for 'Cinemoid'.

## Lamps

500W, E.40 (G.E.S.) base General Lighting Service, clear

# Accessories

Additional 'Cinemoid' colour frame 27 061 0T 'Chromoid'/'Cinemoid' colour frame 27 061 18

