

Strand's Grand Symphony in Light



Minim



Prelude F



Prelude PC



Prelude 30



Prelude 40



Prelude 16/30



Harmony F



Harmony PC



Harmony 12



Harmony 22



Harmony 15/28



Harmony 22/40



Parblazer-4

Minim
300/500W Fresnel Spotlight
Prelude F
500/650W variable beam spread
(9° to 52°) Fresnel Spotlight
Prelude PC
500/650W variable beam spread
(7.5° to 58°) Prism Convex
Spotlight
Prelude 30
500/650W 28° beam spread Profile
Spotlight

Prelude 40
500/650W 40° beam spread Profile
Spotlight
Prelude 16/30
500/650W variable beam spread
(16° to 30°) Profile Spotlight
Harmony F
650/1000W variable beam spread
(7.5° to 65°) Fresnel Spotlight
Harmony PC
650/1000W variable beam spread
(3.5° to 60°) Prism Convex
Spotlight

Harmony 12
650/1000W 11.5° beam spread
Profile Spotlight
Harmony 22
650/1000W 23° beam spread
Profile Spotlight
Harmony 15/28
650/1000W variable beam spread
(15° to 28°) Profile Spotlight
Harmony 22/40
650/1000W variable beam spread
(22° to 40°) Profile Spotlight

Parblazer-4
1000W Par 64 beamlight
All luminaires except Parblazer are
supplied with lamps. Power cables
are detachable on Prelude and
Harmony series and are available
with a fitted 15A 3-pin plug or a
moulded Schuko plugtop or with
wire ends.
Detailed specifications are
available in the form of data
sheets.